

# Interconnection of Core Switches and Firewalls



## Overview

In this video, we configure OSPF routing between a Core Switch and a Firewall and perform complete failover testing to verify redundancy, dynamic route exchange, and high availability. The stack is connected to two Secure Firewalls 3105. “Campus” covers a wide range of networks and locations, from multiple floors in an office tower to a. The aggregated links between the core, aggregation, and access switches have been configured using the network plan import function during site creation, and the aggregated links between the core switch and the network management zone have been configured using commands on the core switch. The. After configuring VLANs on the Core, IP routing is enabled, and everything going as plan, he told me to configure the port between the Core and The Perimeter Firewall on a Separate VLAN and to make it as access Port, whys that?

I mean shouldn't be a trunk between Core and Firewall so that it passes. DHCP normally goes on your Windows Domain Controllers. If you don't have Active Directory, then you should consult with a network architect about putting DHCP on the ASA or core switch. The question and initial idea you had,

suggest, that you have.

## Interconnection of Core Switches and Firewalls



In this video, we configure OSPF routing between a Core Switch and a Firewall and perform complete failover testing to verify redundancy, dynamic route exchange, and high availability.



You want to simply extend L2 all the way from the access switch to the firewall so all ports need to be L2 until they get to the L3 interface on the firewall. One thing to check is your access ...



Solved: Hello, I am asking myself what others recommend for the connection between core switch and Firewall. The setup is the following: Two Catalyst 9300 Core switches in stack.



The aggregated links between the core switch and egress firewalls need to be manually configured on the core switch through iMaster NCE-Campus.



The best way from a security standpoint is to have a physically separate switch connecting the ISP handoff to the firewall, if a switch is needed at all. A switch would only be needed if there ...



With 8x100-GbE QSFP28 slots per FortiGate unit, it provides enough capacity to directly connect with 2x100-GbE ports to each of the two core FortiSwitch units at a nonstop forwarding capacity of up to ...




This hierarchical physical design of a secure campus wired LAN is very common and involves two or three levels between the access switch and the core equipment, such as a firewall or a router.



In that case can I use static routes from Core to ASA and from ASA to Core. Let's say I keep the SVI of vlan 30 on Core itself (instead of FW) and create subinterface on the Firewall, then ...



I have been assigned for my first project ever as network engineer, things seems to be going smoothly, but there's something which is not clear to me. After configuring VLANs on the Core, ...



You can either use a separate connection for each VLAN between the central switch and the firewall - not really efficient -, or you can use a VLAN trunk to connect multiple, tagged VLANs ...

## Contact Us

For more information, pricing, or custom network solutions, please contact us:

Website: <https://www.hashherbcafe.co.za>

Email: [hello@hashherbcafe.co.za](mailto:hello@hashherbcafe.co.za)

Phone: +27 63 814 7295

Address: 15 Galaxy Road, Linbro Business Park, Johannesburg, 2065, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

