

# Maximum range of single-mode fiber optic transceivers




## Overview

Single-mode transceivers commonly operate at 1310 nm and 1550 nm; the broader single-mode range spans roughly 1260–1650 nm. Example reach: a 10G SFP + at 1310 nm typically reaches ~10 km; at 1550 nm similar optics can reach 40–80 km, and specialty OS2 optics extend to ~200 km+ . SFP (Small Form-factor Pluggable) transceivers are essential components in modern fiber optic networks, enabling network devices such as switches, routers, and servers to transmit and receive data over optical fiber. By converting electrical signals into optical signals—and vice versa—SFP. Choosing the right transceiver starts with two physical facts: operating wavelength and fiber core size. Create a link from 16 to 80 km with SEL-2830 Fiber- Optic Transceivers. 652,” which is commonly used in telecommunications networks. Key single mode distance specifications: Optical and copper models can be used on a wide variety of Cisco products and intermixed in combinations of 1000BASE-T, 1000BASE-SX, 1000BASE-LX/LH, 1000BASE-EX, 1000BASE-ZX, or 1000BASE-BX10-D/U on a port-by-port basis. Cisco Optical Gigabit Ethernet SFP Figure 2.

## Maximum range of single-mode fiber optic transceivers



Communicate from 16 to 80 kilometers with port-powered single-mode fiber-optic transceivers.



Single-mode transceivers commonly operate at 1310 nm and 1550 nm; the broader single-mode range spans roughly 1260–1650 nm. Example reach: a 10G SFP + ...



Our 1 Gigabit Singlemode SFP Transceivers offer high-performance, reliable connectivity for singlemode fiber optic networks. These transceivers are engineered for long-distance applications, supporting ...




Typical link distances range from 10km to over 80km, depending on the module type and optical power budget. The primary difference between single mode and multimode SFP transceivers lies in the ...




ER transceivers can cover distances of between 40 km and 8 km over single mode fiber on the 1550 nm wavelength. Used in applications such as metro networks and long-haul telecommunications, they ...



Single-mode transceivers commonly operate at 1310 nm and 1550 nm; the broader single-mode range spans roughly 1260–1650 nm. Example reach: a 10G SFP + at 1310 nm typically reaches ~10 km; at ...



High-performance Single Mode Fiber Optical Transceiver Module with 25G speed, 40km range, and 1310nm wavelength. Reliable, cost-effective, and compatible with industry standards.



The TIA FOTC provides a comprehensive overview of 100GBASE-FR1 capabilities and single-mode optical fiber channel characteristics.



The 1000BASE-ZX SFP operates on standard single-mode fiber-optic link spans of up to approximately 70 km in length. The SFP provides an optical link budget of 21 dB, but the precise link ...



1G SFPs aren't "all the same." Media (fiber vs copper), wavelength, reach, connector, temperature grade, and even application domain (Ethernet, SONET/SDH, PON, Fibre Channel) all matter. Use ...



The maximum distance for single mode fiber optic cable can extend up to several hundred kilometers, making it ideal for long distance data transmission. One type of single mode ...

## Contact Us

For more information, pricing, or custom network solutions, please contact us:

Website: <https://www.hashherbcafe.co.za>

Email: [hello@hashherbcafe.co.za](mailto:hello@hashherbcafe.co.za)

Phone: +27 63 814 7295

Address: 15 Galaxy Road, Linbro Business Park, Johannesburg, 2065, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

