

Non-contact fiber optic temperature sensing instrument



Non-contact fiber optic temperature sensing instrument



The fiber optic temperature sensor system consists of a fiber optic probe and a temperature converter. Our probes include our proprietary materials and processes that helps achieve the highest ...



Non-contact fiber optic sensors are being integrated into smart factory ecosystems, providing continuous, high-fidelity temperature data for predictive maintenance, process optimization, ...



Micronor Sensors offers a complete range of fiber optic temperature sensors, probes and interfaces for high precision temperature measurement in challenging environments.



The Sekidenko 4100T multi-channel, non-contact optical fiber temperature pyrometer measures an object's emitted infrared energy and converts it into usable temperature data (degrees °F or °C) with ...



Based on the intrinsic temperature-dependent quantum effects of bandgap materials, the FOTS sensor features a compact sensing crystal at the fiber tip, ideal for tip measurement applications. Immune to ...



Our fiber optic sensors use a Gallium Arsenide (GaAs) crystal at the fiber tip, making them ideal for highly accurate temperature measurements in environments exposed to microwave radiation and ...



With improved temperature stability, these sensors are particularly suited for temperature measurements in large structures and thermal mapping in electrical machines. Moreover, the FS63 temperature ...



The DTSX fiber optic temperature sensor, which uses optical fiber for the temperature sensor, quickly detects and locates abnormalities in equipment by monitoring temperatures at production facilities ...



High-definition temperature sensing based on the natural Rayleigh backscatter in optical fiber delivers a virtually continuous line of temperature measurements with sub-millimeter spatial resolution.



Get precise temperature measurement with our available contact and non-contact sensors, including thermocouples, RTDs, pyrometers & more for industrial processes.

High-Definition Distributed Temperature Sensing Multipoint Temperature Measurement Long-Range Distributed Temperature Sensing with OptaSense High-definition temperature sensing based on the natural Rayleigh backscatter in optical fiber delivers a virtually continuous line of temperature measurements with sub-millimeter spatial resolution. 1. Map temperature profiles with high spatial resolution (down to 0.65 mm) 2. Small, lightweight and flexible fiber sensors 3. Distributed sensors up ...See more on lunainc

p strong, .b_imgcap_alttitle
.b_factrow strong{color:#767676}#b_results .b_imgcap_alttitle{line-height:22px}.b_imgcap_alttitle{display:flex;flex-direction:row-reverse;gap:var(--mai-smtc-padding-card-nested-default)}.b_imgcap_img{flex-shrink:0;display:flex;flex-direction:column}.b_imgcap_main{min-width:0;flex:1}.b_imgcap_img>div,.b_imgcap_img a{display:flex}.b_imgcap_img img{border-radius:var(--mai-smtc-corner-card-default)}.b_imagePair.square_s>ner{width:50px}.b_imagePair.square_s{padding-left:60px}.b_imagePair.square_s>ner{margin:2px 0 0 -60px}.b_imagePair.square_s.reverse{padding-left:0;padding-right:60px}.b_imagePair.square_s.reverse>ner{margin:2px -60px 0 0}.b_ci_image_overlay: hover{cursor:pointer} sightsOverlay,#OverlayIFrame.b_mcOverlay sightsOverlay{position:fixed;top:5%;left:5%;bottom:5%;right:5%;width:90%;height:90%;border:0;border-radius:15px;margin:0;padding:0;overflow:hidden;z-index:9;display:none}#OverlayMask,#OverlayMask.b_mcOverlay{z-index:8;background-color:#000;opacity:.6;position:fixed;top:0;left:0;width:100%;height:100%}Tempens



Contact Us

For more information, pricing, or custom network solutions, please contact us:

Website: <https://www.hashherbcafe.co.za>

Email: hello@hashherbcafe.co.za

Phone: +27 63 814 7295

Address: 15 Galaxy Road, Linbro Business Park, Johannesburg, 2065, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

