


Parallel Fiber Optic Sensor

Ordering information

NO.	1	2	3	4	5	6
Model	SPF12M1	SPF24M2	SPF48M4	SPF6M1	SPF12M2	SPF24M4
Product name	Patch Panel	Patch Panel	Patch Panel	Patch Panel	Patch Panel	Patch Panel
Illustration						
HU	1	2	4	1	2	4
Maximum number of cores	144	288	576	144	288	576
Product size (excluding modules and adapters)	482.6*371.1*44 mm	482.6*371.1*88.1 mm	482.6*371.1*177 mm	482.6*371.1*44 mm	482.6*371.1*88.1 mm	482.6*371.1*177 mm
Standard color code	RAL9005	RAL9005	RAL9005	RAL9005	RAL9005	RAL9005



Parallel Fiber Optic Sensor



Here, we report an approach for coherently parallel fiber-optic DAS, leveraging integrated dual-soliton microcombs. The dual-comb light source provides colocked multiple-frequency ...



In this paper, a six-axis force sensor based on bending-sensitive optical fibers is proposed. A 3-UPU- (universal joint-prismatic joint-universal joint) compliant parallel mechanism is adopted in ...



In this article, a highly sensitive dual optical fiber parallel Fabry-Pérot interferometer (FPI) pressure sensor is proposed, accompanied by the theoretically analyze about its working principle, along with ...




Fiber-optic sensors are optical sensors based on fiber devices. They are often used for sensing temperature and/or mechanical stress.



A high-sensitive fiber-optic Fabry-Perot sensor with parallel polymer-air cavities based on Vernier effect for simultaneous measurement of pressure and temperature.



A high-temperature measurement fiber sensor based on the Vernier effect is proposed and demonstrated. The sensor comprises two parallel Fabry-Perot interferometers (FPIs) ...



A high-sensitivity fiber optic temperature sensor based on the enhanced harmonic Vernier effect (HVE) is proposed, which consists of two Fabry-Perot interferometers (FPI) that are sensitive to ...



A parallel Vernier fiber-optic sensor based on tapered Fabry-Perot interferometers (FPIs) is proposed and analyzed. Both the sensor and the 3 dB coupler were independently designed to ...



S1 is composed of FPI1 and FPI2 connected in parallel, and S2 is composed of FPI1 and FPI3 connected in parallel. The materials used in this sensor mainly include standard single-mode fiber...



Due to its compact architecture, straightforward fabrication process, and high measurement precision, the proposed sensor holds strong potential for real-world applications ...

Contact Us

For more information, pricing, or custom network solutions, please contact us:

Website: <https://www.hashherbcafe.co.za>

Email: hello@hashherbcafe.co.za

Phone: +27 63 814 7295

Address: 15 Galaxy Road, Linbro Business Park, Johannesburg, 2065, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

